

**JV3-160SP**

**Mimaki**

**Much faster!  
Best quality!**

4 heads help to  
achieve twice  
the printing  
speed of the  
JV3-160S.  
(720x720dpi)

Hi quality printing  
mode to 1440dpi.

Print on  
un coated media.

Water and UV  
resistance for  
3 years outdoors.

**Multiple features with  
New JV3-160SP**



**NEW**

**JV3-160SP**

New Generation Solvent Inkjet Plotter

Print head		
Maximum printing width		
Printing		6-colors
Print nozzle		180 nozzles per color
	360×360dpi	2/4/8 pass, Bi/Uni direction
	360×540dpi	3/6/12 pass, Bi/Uni direction
Print mode	360×720dpi	4/8/16 pass, Bi/Uni direction
	720×720dpi	4/8/16 pass, Bi/Uni direction
	720×1440dpi	8/16/32 pass, Bi/Uni direction
	1440×1440dpi	8/16/32 pass, Bi/Uni direction
Ink	Type	16/32 pass, Bi/Uni direction
	Color	K, C, M, Y
	Ink volume	440cc/color (220cc×2cartridges/color)
		K, C, M, Y, LC, LM+washing liquid×2
		220cc/color (220cc×1cartridge/color)

Item	Specifications
Size	Max.1620mm (63.7inches) , Min.210mm (8.3inches)
Plotting surface	Face OUT
Media	Roll diameter
	Outer $\phi$ 180mm or Less (7.0inches) , Inner 2inch, 3inch
	Roll weight
	25kg (55lbs)
Media cutting	Cutter in Y direction by cutter at head
Media take-up device	Take-up device as standard (inside,outside selectable)
Interface	IEEE-1394 / IEEE-1284
Applicable standards	VCCI, FCC, UL, CE
Power supply	AC100V~120V±10%, AC200V~240V±10% 50/60±1Hz
Power consumption	Less than 1500VA
Ambient conditions	Temperature : 20°C (68°F) - 35°C (95°F) , Humidity : 35%RH - 65%RH (no frost allowable)
External dimensions	(W) 2660× (D) 750× (H) 1240mm [ (W) 104.7× (D) 29.5× (H) 48.8inches]
Weight	Less than 140kg (308lbs)

■ Install proper ventilation, and inspect ventilation equipment regularly. All trade marks or registered trade marks are the property of the respective owners. Specifications shown in this sheet are subject to change without prior notice.

Hybrid Services Ltd  
Meridian House, Road One, Winsford. CW7 3QG  
Tel: 01606 860044  
www.hybridservices.co.uk